



ENVIRO STAIN®

## MULTI-WASH

**DESCRIPTION** Sansin Multi-Wash is a ready to use formula. Used to clean painted and stained surfaces such as decks, fences, logs and siding. It can also be used on Vinyl, Fiberglass, and Concrete and Masonry surfaces. Sansin Multi Wash removes dirt, mold and mildew, water damage and iron stains.

---

### APPLICATIONS

Recommended for use on new and old wood surfaces such as decks, fences, siding, logs, board and batten and timbers. It can also be used on Vinyl, Fiberglass, and Concrete and Masonry surfaces.

---

### PRODUCT BENEFITS

- Biodegradable
- Made in Canada
- Interior and Exterior
- Low VOC
- Non flammable
- Comes with Sansin Wood Lightner®

---

### CHARACTERISTICS

- Coloring.....
- Odor.....
- Form..... Liquid
- Specific Gravity (g/cm<sup>3</sup>)
- Density (lbs/gall)
- pH,.....
- Viscosity, @Zahn 4 @21°C.....
- Solvents.....
- Freezing Point.....
- Diluent.....
- Cleanup.....
- Drying Time (To touch) @ 20°C (68°F)...  
.....Do not allow to dry
- Coverage(Depending on coating  
appearance and thickness).....  
..... 100-200 sqft/ Usgal
- Shelf life.....Looses  
strength slowly over time
- VOC(g/l).....

---

### PACKAGING

Available in 1 US gallon containers

---

### PREPARATION

- Substrate must be dry or damp
- Temperature above 10°C-50°F
- Spray vegetation with water or shield off before and during application
- Protect bordering areas with drop sheets and/or tape off with poly
- Do not allow this product to contact metal, fabric, floor coverings or outdoor furniture
- Keep children and pets away from work area while using Multi Wash

---

### APPLICATION METHODS

- Apply a liberal and uniform application using brush, roller or spray
- On vertical surfaces start at the bottom and work your way up

---

### WORKING PROCEDURE

- Do not allow to dry as this will require reapplication
- Do not apply in direct sunlight
- Allow the product to dissolve coating for at least 15 minutes
- Thoroughly rinse the surface using a garden hose or low pressure power washer (max pressure 500psi)
- Direct the power washer wand with the grain of the wood
- Do not stop the wand on the wood as this may mark the wood surface
- Allow the wood to dry completely
- See Directions For Use

---

### STORAGE

- Close container lightly
- Store in cool dry
- Avoid exposure to sunlight
- Do not reuse container
- Do not allow freezing

- Rinse container thoroughly before disposal

---

**SAFETY** See Material Safety Data Sheet

---

**WARNING TO USERS**

Contains Phosphoric Acid. Avoid contact with skin and mucous membranes. Wear protective gear during application: ie rubber gloves, rubber pants, rubber coat, rubber boots goggles, and a NIOSH/MSHA approved respirator when spraying. Project surfaces become extremely slippery when working. Avoid walking on surface while wet. Keep out of reach of children, if swallowed immediately drink two glasses of orange juice.

The information contained in this document is given in good faith based on our current knowledge. The use of the product is beyond the control of The Sansin Corporation, and no guarantees, expressed or implied, are made as to the result to be obtained if not used in accordance with the published Directions for Use. The Sansin Corporation does not assume any legal responsibility for use or reliance on same. This information must on no account be used as a substitute for necessary field tests, which alone can ensure that the product is suitable for the expected use. Before using any product, read its label.

September 2009