



ENVIRO STAIN®

SDF HT

DESCRIPTION Sansin's Precision Coat SDF HT is an environmentally-friendly finish specially designed for heat treated wood. It is UV resistant, low in VOC's, and non-flammable with easy soap and water clean-up. This unique formula provides a rich and attractive coating that offers lasting protection. Sansin Precision coat SDF HT will not crack, peel or blister. Maintenance coats may be applied every two to three years on horizontal surfaces and two to four years on vertical surfaces.

APPLICATIONS

- Siding
- Decks
- Fences
- Outdoor furniture
- Log Homes

- Solids..... 21% ±0.5%
- Drying time (between applications) @ 20°C (68°F)24 hour
- Coverage,200-300 sqft/USgal
- Longer drying time needed in high humidity or low temperature
- VOC (g/l)Actual – 48
Regulatory – 125

PRODUCT BENEFITS

- Environmentally Responsible
- Penetrating Formula
- Can be applied on damp wood.
- Creates dimensional stability
- Non flammable
- Breathing
- UV Resistant

PACKAGING

Available in Quarts, 1 and 5 US gallon plastic containers

TINTABLE BASES

For best results on heat treated wood Sansin's Precision Coat SDF HT should be tinted with a minimum of 5 Y of colorant per gallon.

CHARACTERISTICS

- AppearanceNatural, Translucent & Saturated
- Coloring..... Saturated and Custom
- Odor Low
- Form Liquid
- Specific Gravity 1.00-1.03
- Density8.3-8.4
- pH (approx)8.8-9.0
- Viscosity, #2 ZAHN Cup, 20°C (68°F).....
..... 18-22 sec
- Solvents..... Low
- Freezing Point-1°C (31°F)
- Diluent Water
- Cleanup Soap and Water
- Drying time (to touch) @ 20°C (68°F)
..... 4-6 hours

PREPARATION

- Inspect the entire surface for defects and deterioration. Repair and replace defects where necessary. Use Sansin cleaners and/or wash the entire surface with a minimum 3000 PSI pressure washer using only clean water (SEE PUBLISHED DIRECTIONS FOR USE).
- Sand machined or planed surfaces using a plate sander or an orbital sander with 60 grit sandpaper. Follow by power washing (500 PSI), vacuum or compressed air for proper cleaning. Allow to dry.

APPLICATION METHODS

- Apply Sansin Precision Coat SDF HT by any agreeable method – dipping, brush, or spray (low pressure or airless).

WORKING PROCEDURE

- Test formula on an inconspicuous wood surface to ensure proper color and penetration.
- Apply in proper conditions, ideal temperature of 70° F (21° C) and relative humidity of approximately 50%.
- For best results, apply a flood coat of Sansin Precision Coat SDF HT, to a point of maximum absorption. Always back-brush the surface a few minutes after application.
- Continually check the surface; wipe up all puddles and brush out any runs.
- For additional protection an additional coat of SDF HT may be applied.
- Do not apply in the heat of day or in direct sunlight as this will cause surface filming and limit penetration which may result in peeling at a later date.
- Do not apply if rain or near-freezing temperatures are likely to occur within 24 hours after application.
- When using a tinted product be sure to stir well before and during application.
- Always read published directions for use prior to beginning a project.

MAINTENANCE

Vertical surfaces require maintenance every 3-6 years. Maintenance is necessary when the surface shows signs of wear, such as fading or erosion. Maintaining your wood on a regular basis will ensure long-lasting color retention, exceptional dimensional stabilization and effective water repellency. Periodically, clean the wood surface with a power washer or Sansin Multi-Wash to remove dirt and residue. How frequently maintenance coats

are required will depend on the quality of prior preparation, quality of application and weather exposure levels. If fading or erosion is evident, prepare wood by using a power washer to lightly clean the wood surface; or use Sansin Multi-Wash. Then re-apply one maintenance coat of Sansin SDF HT according to instructions.

STORAGE

Shelf life when stored in ideal conditions is 18 months. Store at a temperature of between +10°C and + 30°C. Keep containers tightly closed.

SAFETY See Material Safety Data Sheet

WARNING TO USERS

Keep out of reach of children, if swallowed immediately drink two glasses of milk or warm water. Do not induce vomiting. Call physician immediately. Avoid contact with skin or eyes; flush with soap and water. Avoid breathing of vapor or mist. Wear a properly fitted NIOSH/MSHA approved respirator.

The information contained in this document is given in good faith based on our current knowledge. The use of the product is beyond the control of The Sansin Corporation and no guarantees, expressed or implied, is made as to the result to be obtained if not used in accordance with the published Directions for Use. The Sansin Corporation does not assume any legal responsibility for use or reliance on same. This information must on no account be used as a substitute for necessary field tests, which alone can ensure that the product is suitable for the expected use. Before using any product, read its label

September 2009