MATERIAL SAFETY DATA SHEET

SECTION 1: PRODUCT IDENTIFICATION AND USE

PRODUCT IDENTIFIER BORACOL 20	PRODUCT IDENTIFICATION NUMBER (PIN) N/AP			
PRODUCT USE WOOD PRESERVATIVE FOR STRUCTURES				
MANUFACTURER'S NAME		SUPPLIERS NAME THE SANSIN CORPORATION		
STREET ADDRESS		STREET ADDRESS 111 MacNab Ave.		
CITY	PROVINCE	CITY STRATHROY	PROVINCE ON	
POSTAL CODE	EMERGENCY TELEPHONE.NO:	POSTAL CODE N7G 4J6	EMERGENCY TELEPHONE #: 519-245-4623	

SECTION 2: HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENTS	%	CAS NUMBER	LD50 OF INGREDIENT (SPECIFY SPECIES AND ROUTE)	LC50 OF INGREDIENT (SPECIFY SPECIES)
MONOPROPYLENE GLYCOL	50-80	000057-55-6	21,000-33,700MG/KG ORAL RAT	50 PPM (AEROSOL 10MG/M³)
DISODIUM OCTABORATE TETRAHYDRATE	19.6	12280-03-4	2500MG/KG OARL RAT	ACGIH: 10 MG/ M³)
DIDECYL DIMETHYL AMMONIUM CHLORIDE(DDAC)	1.0	7173-51.5	450MG/KG ORAL RAT	

SECTION 3: PHYSICAL DATA

PHYSICAL STATE LIQUID	ODOUR AND APPEARANCE CLEAR, VISCOUS LIQUID WITH VERY LITTLE ODOUR			ODOUR ; TRESHOLD PPM N/AV
VAPOUR PRESSURE (MM HG) ALMOST NEGLIGIBLE	VAPOUR DENSITY (AIR=1) N/AV	EVAPORATION RATE N/AV	BOILING POINT APROX: 101°C.	FREEZING POINT N/AV
PH 7.3	SPECIFIC GRAVITY 1.15 GRAM/LITRE	COEFF. WATER/OIL DIS	ST.	COEFFICIENT OF WATER/OIL DIST:N/A

SECTION 4: FIRE AND EXPLOSION DATA

FLAMMABILITY				
'ES (NO v IF YES, UNDER				
WHICH CONDITIONS	WHICH CONDITIONS			
MEANS OF EXTINCTION: N/AP				
FLASHPOINT (°C) AND METHOD	UPPER FLAM	MABLE LIMIT	LOWER FLAMMABLE LIMIT	
> 107°C PMCC	(% BY VOLUM	ME) N/AV	(% BY VOLUME) :N/AV	
AUTOIGNITION TEMPERATURE (°C)	HAZARDOUS	COMBUSTION PRODUCTS: INC	COMPLETE COMBUSTION MAY	
>350°C	GENERATE C	CARBON MONOXIDE AND PROP	IONALDEHYDE	
EXTINGUISHING MEDIA: FOAM, CARBON DIOXII	DE, WATER	SPEC.FIRE FIGHTING PROCE	DURES: WEAR POSITIVE-	
FOG, AND DRY CHEMICALS		PRESSURE, SELF-CONTAINE	D BREATHING APPARATUS	
		AND PROTECTIVE FIRE FIGHTING CLOTHING (INCLUDES		
		FIRE FIGHTING HELMET, COAT, BOOTS, GLOVES)		
EXPLOSION SENSITIVITY TO II	MPACT	SENTIVITY TO STATIC DISCHA	ARGE	
DATA NONE		NONE		

SECTION 5: REACTIVITY DATA

CHEMICAL STABILITY: STABLE	HAZARDOUS DECOMPOSITION: PROBABLY NONE	
CONDITIONS TO AVOID: STRONG OXIDIZING AGENTS AND STRONG REDUCING AGENTS.		
INCOMPATIBILITY (MATERIALS AVOID): STRONG, OXIDIZING AGENTS AND STRONG REDUCING TO AGENTS		
NONE		
HAZARDOUS POLYMERIZATION		
MAY NOT O	CLID	
IVIA T NOT OC	CUK	

PRODUCT IDENTIFIER: BORACOL 20-BD

SECTION 6: TOXICOLOGICAL PROPERTIES

Г	\sim	ΙT	_	7	- 1 1	ΓRY·	
r	くしり		- () H	- 1/1	IKY	

SKIN CONTACT v SKIN ABSORPTION v EYE CONTACT v **INHALATION: MAYBE** INGESTION v EFFECTS OF ACUTE EXPOSURE TO PRODUCT: MAY CAUSE IRRITATION TO EYES. SKIN MAY BECOME RED AND SOFT FROM EXPOSURE. DDAC MAY BE CORROSIVE TO SKIN. PROLONGED INHALATION IS NOT LIKELY TO CAUSE ADVERSE EFFECTS, MISTS ARE NOT LIKELY TO BE HAZARDOUS, INGESTION: THIS MATERIAL MAY BE HARMFUL IF SWALLOWED

EFFECTS OF CHRONIC EXPOSURE TO PRODUCT: 1, CARCINOGENICITY: CONTAINS NO KNOWN CARCINOGENS

	2. MUTAGENICITY : CONTAINS NO KNOWN MUTAGENS. 3. OTHERS: NONE CURRENTLY KNOWN				
	EXPOSURE LIMITS	IRRITANCY OF PRODUCT	SENSITIZATION TO	CARCINOGENICITY	
		SKIN: IRRITATION	PRODUCT	NONE KNOWN	
	N/AV	EYES: IRRITATION	NONE KNOWN		
		REDNESS, BLURRED VISION			
	TERATOGENICITY	REPRODUCTIVE TOXICITY	MUTAGENICITY	SYNERGISTIC PRODUCTS	
NONE KNOWN NONE KNOWN					
		NONE KNOWN	NONE KNOWN		

SECTION 7: PREVENTIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT:		
GLOVES(SPECIFY) RUBBER, PVC	RESPIRATOR(SPECIFY) IF SPRAYING: NIOSH / MSHA APPROVED	EYE(SPECIFY) GOGGLES OR FACE SHIELD
FOOTWEAR(SPECIFY) RUBBER, PVC	CLOTHING(SPECIFY): LONG SLEEVES SHIRT, LONG PANTS AND HAT. RUBBER APRON	OTHER(SPECIFY)

ENGINEERING CONTROLS(SPECIFY, EG. VENTILATION, ENCLOSED PROCESS):

LOCAL EXHAUST VENTILATION TO MAINTAIN EXPOSURE BELOW TLV.'S

LEAK AND SPILL PROCEDURE: CONTAIN SPREAD, SOAK UP WITH INERT ABSORBENT, CONTACT THE PROVINCIAL REGULATORY AGENCY OR THE MANUFACTURER

WASTE DISPOSAL: RINSE THE EMPTIED CONTAINER THOROUGHLY AND ADD THE RINSINGS TO THE TREATMENT SITE. MAKE EMPTY CONTAINER UNSUITABLE FOR FURTHER USE.

DISPOSE OF IN ACCORDANCE WITH LOCAL, PROVINCIAL & FEDERAL REGULATIONS

HANDLING PROCEDURES AND EQUIPMENT: KEEP CONTAINER CLOSED STORE IN COOL WELL VENTILATED AREA AWAY FROM SOURCE OF IGNITION AND INCOMPATIBLE MATERIALS

STORAGE REQUIREMENTS: CLOSE CONTAINERS, STORE IN COOL WELL VENTILATED AREA AWAY FROM SOURCE OF IGNITION AND INCOMPATIBLE MATERIALS

OTHER: AS WITH ALL WOOD PRESERVATIVE MATERIALS, GOOD HYGIENIC PRACTICES SHOULS BE FOLLOWED. WASH HANDS THOROUGHLY IMMEDIATELY AFTER USE AND PRIOR TO EATING OR SMOKING.

SPECIAL SHIPPING INFORMATION: N/AP

SECTION 8: FIRST AID MEASURES

SKIN: WASH WITH SOAP AND WATER, LAUNDER CONTAMINATED CLOTHING BEFORE RE-USE.

EYES: FLUSH WITH WATER FOR AT LEAST 20 MINUTES, LIFT UPPER AND LOWER LIDS

INHALATION: REMOVE TO FRESH AIR, IF BREATHING IS DIFFICULT ADMINISTER OXYGEN. IF BREATHING HAS STOPPED, GIVE ARTIFICIAL RESPIRATION. KEEP WARM AND AT REST.

INGESTION: DRINK 1-2 GLASSES OF WATER INDUCE VOMITING. BY TOUCHING BACK OF THROAT WITH FINGER, KEEP WARM AND AT REST.

IN ALL CASES GET IMMEDIATE MEDICAL ATTENTION

SECTION 9: PREPARATION DATE OF MSDS

PREPARED BY :TECHNICAL DEPARTMENT		PHONE NUMBER	DATE
		(519) 245-2001	JANUARY 2016

SASCO PRODUCTS LIMITED AND ITS AFFILIATES ASSUME NO RESPONSIBILITY FOR INJURY TO ANYONE CAUSED BY THE MATERIAL IF REASONABLE SAFETY PROCEDURES ARE NOT ADHERED TO AS STIPULATED IN THE MATERIAL SAFETY DATA SHEET, ADDITIONALLY, SASCO PRODUCTS LIMITED AND ITS AFFILIATES ASSUME NO RESPONSIBILITY FOR INJURY TO ANYONE CAUSED BY ABNORMAL USE OF THE MATERIAL EVEN IF REASINABLE SAFETY PROCEDURES ARE FOLLOWED.

FURTHERMORE, VENDEE AND THIRD PERSONS ASSUME THE RISK IN THEIR USE OF THE MATERIAL.

This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of The Sansin Corporation's knowledge or is obtained from sources believed by The Sansin Corporation to be accurate. The Sansin Corporation does not assume any legal responsibility for use or reliance on same. Customers are encouraged to conduct their own tests. Before using any products, read its label.