

THE SANSIN CORPORATION

MATERIAL SAFETY DATA SHEET

SECTION 1: PRODUCT IDENTIFICATION AND USE

PRODUCT IDENTIFIER TIMBER-TEC SEAL'N HIDE			PRODUCT IDENTIFICATION NUMBER (PIN) N/AP	
PRODUCT USE MOISTURE CURE LOG HOME CHINKING				
MANUFACTURER'S NAME THE SANSIN CORPORATION.			SUPPLIERS NAME	
STREET ADDRESS 111 MACNAB AVENUE			STREET ADDRESS	
CITY STRATHROY	PROVINCE ON	CITY	PROVINCE	
POSTAL CODE N7G 4J6	EMERGENCY TELEPHONE.NO: CANUTEC 613-996-6666	POSTAL CODE	EMERGENCY TELEPHONE #: US/NORTH AMERICA: 800-424-9300 OUTSIDE THE US: 703-527-3887	

SECTION 2: HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENTS	%	CAS NUMBER	LD50 OF INGREDIENT (SPECIFY SPECIES AND ROUTE)	LC50 OF INGREDIENT (SPECIFY SPECIES)
SILYL TERMINATED POLYETHER				
PROPRIETARY COMPOUNDS			20 GR/KG RAT, ORAL	

SECTION 3: PHYSICAL DATA

PHYSICAL STATE HIGH VISCOUS	ODOUR AND APPEARANCE LIGHT ESTER ODOUR			ODOUR ; TRESHOLD PPM N/AV
VAPOUR PRESSURE (MM HG) N/AP	VAPOUR DENSITY (AIR=1) N/AP	EVAPORATION RATE N/AP	BOILING POINT >195°C (384°F)	FREEZING POINT
PH	SPECIFIC GRAVITY 1.0 TO 1.1	COEFF. WATER/OIL DIST. N/AV		

SECTION 4: FIRE AND EXPLOSION DATA

FLAMMABILITY YES (NO v IF YES, UNDER WHICH CONDITIONS				
MEANS OF EXTINCTION: N/AP				
FLASHPOINT (°C) AND METHOD >215°C (420°F), CLEVELAND OPEN CUP		UPPER FLAMMABLE LIMIT (% BY VOLUME) N/AP		LOWER FLAMMABLE LIMIT (% BY VOLUME) :N/AP
AUTOIGNITION TEMPERATURE (°C) NONE		HAZARDOUS COMBUSTION PRODUCTS NONE		
EXPLOSION DATA N/AP	SENSITIVITY TO IMPACT NONE		SENTIVITY TO STATIC DISCHARGE NONE	

SECTION 5: REACTIVITY DATA

CHEMICAL STABILITY YES v NO <input type="checkbox"/> IF NO, UNDER WHICH CONDITIONS	
INCOMPATIBILITY WITH OTHER SUBSTANCES : REACTION WITH WATER CAN RELEASE SMALL AMOUNTS OF YES <input type="checkbox"/> NO <input type="checkbox"/> IF SO WHICH ONES: METHANOL (<1%)	
REACTIVITY, AND UNDER WHAT CONDITIONS NONE	
HAZARDOUS DECOMPOSITION PRODUCTS THERMAL DECOMPOSITION MAY PRODUCE TOXIC FUMES OF CO AND/OR CO ₂	

PRODUCT IDENTIFIER : TIMBER-TEC SEAL'N HIDE

SECTION 6: TOXICOLOGICAL PROPERTIES

ROUTE OF ENTRY: SKIN CONTACT <input checked="" type="checkbox"/> SKIN ABSORPTION <input type="checkbox"/> EYE CONTACT <input checked="" type="checkbox"/> INHALATION <input type="checkbox"/> INGESTION <input checked="" type="checkbox"/>			
EFFECTS OF ACUTE EXPOSURE TO PRODUCT: NONE KNOWN			
EFFECTS OF CHRONIC EXPOSURE TO PRODUCT: MAY CAUSE MODERATE IRRITATION			
EXPOSURE LIMITS N/AV	IRRITANCY OF PRODUCT SKIN: IRRITATION EYES: IRRITATION REDNESS, BLURRED VISION	SENSITIZATION TO PRODUCT NONE KNOWN	CARCINOGENICITY NONE KNOWN
TERATOGENICITY NONE KNOWN	REPRODUCTIVE TOXICITY NONE KNOWN	MUTAGENICITY NONE KNOWN	SYNERGISTIC PRODUCTS NONE KNOWN

WHEN REACTED WITH WATER TRACE AMOUNTS OF METHANOL MAY BE GENERATED WHICH MAY CAUSE DIZZINESS, DROWSINESS, BLURRED VISION, TINGLING IN HANDS AND FOREARMS.

SECTION 7: PREVENTIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT:			
GLOVES(SPECIFY) RUBBER, PVC	RESPIRATOR(SPECIFY) IF SPRAYING: NIOSH / MSHA APPROVED	EYE(SPECIFY) GOGGLES	
FOOTWEAR(SPECIFY) RUBBER, PVC	CLOTHING(SPECIFY) RUBBER APRON	OTHER(SPECIFY) N/AP	
ENGINEERING CONTROLS(SPECIFY,EG.VENTILATION, ENCLOSED PROCESS) : LOCAL EXHAUST VENTILATION TO MAINTAIN EXPOSURE BELOW TLV.'S			
LEAK AND SPILL PROCEDURE : CONTAIN SPREAD, SOAK UP WITH INERT ABSORBENT			
WASTE DISPOSAL : DISPOSE OF IN ACCORDANCE WITH LOCAL, PROVINCIAL & FEDERAL REGULATIONS			
HANDLING PROCEDURES AND EQUIPMENT : NO SPECIAL EQUIPMENT NEEDED			
STORAGE REQUIREMENTS : CLOSE CONTAINERS, DO NOT ALLOW TO FREEZE			
SPECIAL SHIPPING INFORMATION : N/AP			

SECTION 8: FIRST AID MEASURES

SKIN : WASH WITH DILUTED ETHANOL TO REMOVE CURED PRODUCT AND WASH WITH SOAP AND WATER, LAUNDER CONTAMINATED CLOTHING BEFORE RE-USE.
EYES : FLUSH WITH WATER FOR AT LEAST 20 MINUTES, LIFT UPPER AND LOWER LIDS
INHALATION: REMOVE TO FRESH AIR, IF BREATHING IS DIFFICULT ADMINISTER OXYGEN. IF BREATHING HAS STOPPED, GIVE ARTIFICIAL RESPIRATION. KEEP WARM AND AT REST.
INGESTION: DO NOT INDUCE VOMITING. KEEP WARM AND AT REST.
IN ALL CASES GET IMMEDIATE MEDICAL ATTENTION

SECTION 9: PREPARATION DATE OF MSDS

PREPARED BY :TECHNICAL DEPARTMENT	PHONE NUMBER (519) 245-2001	DATE JANUARY 2016
-----------------------------------	--------------------------------	----------------------

This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of The Sansin Corporation's knowledge or is obtained from sources believed by The Sansin Corporation to be accurate. The Sansin Corporation does not assume any legal responsibility for use or reliance on same. Customers are encouraged to conduct their own tests. Before using any products, read its label.