

Wood Lightener: Brightens all wood surfaces, particularly wood treated with Sansin Wood Wash. Treated surfaces often appear darker than expected and Wood-Lightener will restore the original natural color of the wood.

FEATURES

- Biodegradable
- Interior and Exterior
- Low VOC
- Non flammable
- Comes with Wood-Strip and Wood Wash

IMPORTANT

Product Data Sheets are based on "ideal" work conditions. Due to wood variability and varying environmental conditions, it is strongly recommended that the end-user needs to determine that the application conditions, coating product system, and techniques are suitable to reach the desired results. Please see Conditions of Sale.

APPLICATIONS

Used to neutralize and restore wood surfaces treated with Sansin Wood Wash and Wood-Strip.

CHARACTERISTICS

- Coloring.....White Granular
- Odor.....Low
- Form.....Solid
- Specific Gravity (g/cm³).....N/A
- Density (lbs/gal).....N/A
- pH.....2.5-3
- Viscosity, @Zahn 2 @21°C.....16 sec +/- 1sec
- Solvents.....N/A
- Freezing Point.....0°C
- Diluent.....Water
- Cleanup.....Soap & Water
- Drying Time (To touch) @ 20°C (68°F).....Do not allow to dry
- Coverage (Depending on coating appearance and thickness).....150-300 sq/ft
- Shelf life.....Loses strength slowly over time
- Solids.....<1%
- VOC(g/l).....0 g/L

PACKAGING

Available in 8.8 oz (250 g) bag.

PREPARATION

- Substrate must be dry above 10°C (50°F).
- Spray vegetation with water or shield off before and after application.
- Protect all border areas with drop sheets and/or tape off with poly all areas not being cleaned.
- Do not allow this product to contact metal, fabric, floor coverings or outdoor furniture.
- Keep children and pets away from work area while using Wood Lightener.

APPLICATION METHODS

- Dissolve Wood-Lightener in 1.5 – 2.0 gal (5.75 – 7.5L) of water depending on the amount of brightening you require.
- Always ensure a liberal and uniform application.
- Apply using a brush, roller or spray to a dry wood surface.
- On vertical surfaces start at bottom and work up.
- Allow Wood-Lightener to work 5-15 minutes to revive the natural wood color.
- Do not allow Wood-Lightener™ to dry.
- Do not apply in direct sunlight.

- Thoroughly rinse with water using a garden hose or pressure washer (maximum pressure 500 PSI).
- Ensure thorough rinse as a slight residue can affect the coating performance.
- Allow wood to completely dry.

STORAGE

- Close and seal package.
- Store in a cool dry place.
- Avoid exposure to sunlight.
- Do not allow freezing.
- Rinse container thoroughly before disposal according to regulations.

SAFETY

Caution: Eye Irritant. Contains Citric Acid. If splashed in eyes, rinse eyes with water for 20 minutes. Consult physician. See Material Safety Data Sheet.

WARNING TO USERS

Wear protective gear during application: i.e. rubber gloves, rubber pants, rubber coat, rubber boots goggles, and a NIOSH/MSHA approved respirator when spraying. Project surfaces become extremely slippery when working. Avoid walking on surface while wet. Keep out of reach of children, if swallowed immediately drink two glasses of orange juice.

The information contained in this document is given in good faith based on our current knowledge. The use of the product is beyond the control of The Sansin Corporation, and no guarantees, expressed or implied, are made as to the result to be obtained if not used in accordance with the published Directions for Use. The Sansin Corporation does not assume any legal responsibility for use or reliance on same. This information must on no account be used as a substitute for necessary field tests, which alone can ensure that the product is suitable for the expected use. Before using any product, read its label

CONDITIONS OF SALE

The only obligation of the manufacturer and seller shall be to replace such quantity of Sansin product that is proven to be defective. Proof of purchase is required. Seller or manufacturer shall not be liable for any loss or damage connected with the use and/or handling of this product. All labor costs are specifically excluded. User should determine suitability of product for the intended use before application. User assumes all risk and liability in connection therewith. This warranty is expressly made in lieu of any and all other rights, warranties, conditions and remedies, express or implied, including but not limited to any implied warranty or condition of merchantability, fitness for a particular purpose, and any warranty or condition arising out of a course of dealing, a custom or usage of trade. If any distributor or seller of product offers warranties or remedies which differ from those offered by Sansin, Sansin accepts no responsibilities for such warranties or remedies.

Wood Lightener

ENVIRO STAIN®

EASY TO
USE 

NON
FLAMMABLE

RESTORES
WOOD

ECO
FRIENDLY 